

MP GEAR AND MULTI-GEAR OIL

PREMIUM MULTIPURPOSE GEAR OIL

Product Description: MP GEAR OIL is a multi-purpose sulfur-phosphorus type hypoid gear lubricant meeting requirements of API Service Classification GL-5. It is manufactured from highest quality base oils fortified with VI improvers, rust inhibitors, foam suppressants, antiwear and extreme pressure additives and pour point depressants. The multi-viscosity oil formulations permit use over a wide temperature range.

Features:

- Protects hypoid gears from wear and scuffing.
- Provides rust protection to gears.
- Multi-purpose for minimum inventory.
- Multi-viscosity provides year round use.
- Non-foaming.
- Compatible with other automotive gear oils.

Typical Uses:

- Meets API GL-5 and MT-1.
- Meets SAE J2360 requirements.
- Meets Mack specifications GO-F, GO-G, GO-H, GO-J.
- Meets Rockwell Specification 0-76A, 0-76B and 0-76D.
- Recommended for differentials and conventional transmissions in passenger cars and trucks where GL-5 fluids are specified.
- Suitable as make-up in limited slip differentials. (Factory specified lubricant required on complete refill of new or rebuilt units)

Typical Specifications:

GRADE, SAE	MP GEAR OILS			MULTI GEAR OILS		
	80	90	140	80W-90	80W-140	85W-140
Gravity °API	26.5	25.1	23.8	26.0	26.9	24.5
Flash Point, °F.	410	420	440	415	440	430
Fire Point, °F.	430	450	490	445	490	465
Pour Point, °F.	-15	5	10	-25	-25	5
Viscosity:						
cSt. @ 100° C.	9.0	16	26.0	16.26	26.0	25.5
Viscosity Index	98	95	90	98	110	96
Color, D-1500	4.5	6.5	7.0	5.5	4.5	7.0

CONTAINS HIGH PERFORMANCE ADDITIVE CHEMISTRY.
VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.