

OPEN GEAR AND CABLE LUBRICANT

ADHESIVE, WATER-RESISTANT OPEN GEAR LUBRICANT

Product Description: OPEN GEAR AND CABLE LUBRICANT is an asphalt-free lubricant, specially formulated for ease of application through a centralized system or by hand application.

Features:

- Long lasting protection because of tackiness and durability of coating.
- Water resistant - offers rust protection in wet applications.
- Provides corrosion protection to cable and chains.
- Extreme pressure properties protect heavily loaded gears from scoring and galling.
- No longer contains asphalt

Typical Uses:

- Lubrication of wire ropes, cables, flexible couplings, chains, open gears, and partly enclosed gears.
- Also used on sliding surfaces of drag lines and shovels.
- Open gears of mine hoists, ball mills, rubber mixers, cement mills, coke ovens, construction equipment, and other applications where adhesive grease is required.

Typical Specifications:

PARAMETERS

TYPICAL RESULTS

| | |
|-----------------------|-------|
| Gravity °API | 23.1 |
| Flash Point, °F. PMCC | 165 |
| Pour Point, °F. | 50 |
| Viscosity: | |
| cSt. @ 40° C. | 3,500 |
| Color, D-1500 | D8 |

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.