

UNIGEAR

SUPER-PREMIUM VERSATILE, EXTRA HEAVY DUTY GEAR LUBRICANT - GL-5 PLUS

Product Description: UNIGEAR is a multi-purpose sulfur-phosphorus type hypoid gear lubricant exceeding requirements of API Service Classification GL-5. It is manufactured from highest quality base oils fortified with VI improvers, rust inhibitors, foam suppressants, anti-wear and extreme pressure additives and pour point depressants. The multi-viscosity grades may be used over wide temperature ranges.

Features:

- Exceptional thermal and oxidative stability to protect parts and ensure maximum performance.
- Protects hypoid gears from wear and scuffing.
- Provides rust protection to gears.
- Multi-purpose for minimum inventory.
- Multi-viscosity provides year round use. Non-foaming.
- Compatible with other automotive gear oils.

Typical Uses:

- Exceeds API GL-5 and MT-1.
- Meets SAE J2360 requirements.
- Exceeds Mack Specifications GO-F, GO-G, GO-H, and GO-J.
- Rockwell Specification 0-76A and 0-76D.
- Recommended for differentials and conventional transmissions in passenger cars and trucks where GL-5 fluids are specified.
- Suitable as make-up in limited slip differentials. (Factory specified lubricant required on complete refill of new or rebuilt units.)

Typical Specifications:

GRADE, SAE	90	140	75W-90	80W-90	80W-140	85W-140
Gravity °API	25.4	24.3	28.2	26.0	27.5	23.4
Flash Point, °F.	400	420	420	395	415	410
Fire Point, °F.	400	460	460	420	445	445
Pour Point, °F.	5	10	-4.5	25	-25	5
Viscosity: cSt. @ 100° C.	16.0	26.0	15	16.26	26.0-	25.5
Brookfield, cP@-40°C.			100,000	-	90,000	-
Brookfield, cP@-26°C.			-	90,000	-	-
Brookfield, cP@-12°C.	95		-	-	-	85,000
Viscosity Index		90	45	98	110	96
Color, D-1500	4.0	4.5	3.5	3.5	4.0	5.0

**CONTAINS HIGH PERFORMANCE ADDITIVE CHEMISTRY.
VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.**