

WORM GEAR OIL 250

WORM GEAR LUBRICANT

API GL-2 TYPE

Product Description: WORM GEAR OIL 250 is manufactured from high VI paraffin base oils blended with special mild extreme pressure additives required for sliding action encountered in the lubrication of worm gears. Gear lubricant is non-corrosive to copper and bronze gears commonly found in worm gears, as it contains an effective oxidation and corrosion inhibitors, as well as foam suppressant.

Features:

- Non-corrosive to bronze gears on copper bearings.
- Excellent mild extreme pressure additive suitable for worm gears.
- Non-foaming.
- Compatible with straight mineral gear lubricants.

Typical Uses:

- Recommended where GL-2 type lubricant is required.
- Timken Axle Specification 0-74.
- AGMA 8A.
- Recommended for Worm drives and reduction gears for trucks, tractors and industrial worm reduction gears where an SAE 250 lubricant is required.
- Flexible coupling lubricant.
- Journal bearing lubricant.

THIS PRODUCT IS NOT TO BE USED IN HYPOID GEARS.

Typical Specifications:

GRADE, SAE	250
Gravity °API	22.8
Flash Point, °F.	460
Fire Point, °F.	520
Pour Point, °F.	10
Viscosity:	
cSt. @ 40°C.	969
cSt@100°C.	47.4
Viscosity Index	92
Color, D-1500	D8.0

**CONTAINS HIGH PERFORMANCE ADDITIVE CHEMISTRY.
VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.**