

EDGER ARBOR OIL

ARBOR SAW OIL

Product Description: EDGER ARBOR OIL is a select, light-colored base oil containing an effective gum and pitch softening agent to prevent pitch build up on saw arbors which allows saws to move freely on arbors.

Features:

- Economical - low cost.
- Lubricity additive provides smooth surface finish.
- Mist suppressant minimizes fogging.
- Reduces cutting tool wear.

Typical Uses:

- Lubrication of saw arbors or other bearings where wood pitch, resins, or gum interfere with proper lubrication.
- Can be used as a concrete form oil either straight or cut-back with diesel fuel.
- Used as mineral-fatty oil for cutting or working non-ferrous metal.
- Additive in this product reacts adversely with zinc.

DO NOT USE WITH GALVANIZED PIPE OR IN MECHANICAL LUBRICATORS MANUFACTURED FROM HOT METAL.

Typical Specifications:

PARAMETERS	TYPICAL RESULTS
Gravity °API	24.7
Flash Point, °F.	315
Fire Point, °F.	345
Viscosity:	
SUS @ 100 °F.	120
SUS @ 210 °F.	39
cSt. @ 40°C.	22.7
cSt@100°C.	3.78
Color, D-1500	2.5

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.