

HD CHAIN OIL

PREMIUM QUALITY CHAIN OIL

Product Description: HD CHAIN OIL is manufactured from a high quality medium VI solvent extracted naphthenic base oil fortified with molybdenum disulfide and a tackiness agent to impart maximum antiwear and clinging characteristics.

Features:

- Economical - tackiness agent reduces oil consumption.
- Friction modifier (Moly) reduces wear.
- Tackiness agent reduces journal bearing and leakage.
- Reduces inventory - one oil for many uses.

Typical Uses:

- Recommended for lubrication of chains, rollers, and conveyors in industrial plants, contractors equipment, and agricultural equipment such as mechanical tomato and grape harvesters.
- Recommended for slow speed heavy loaded journal bearings, slides, ways, crossheads and sprockets.
- Chain saw bar and chain lubricant.

Typical Specifications:

GRADE, ISO	68	100	220
Gravity °API	24.4	24.3	27.6
Flash Point, °F.	440	450	485
Fire Point, °F.	485	495	535
Pour Point, °F.	-10	-10	5
Viscosity:			
SUS @ 100 °F.	340	527	1,165
SUS @ 210 °F.	52	59	96
cSt. @ 40°C.	68	100	220
cSt@100°C.	7.6	9.6	18.6
Color	Grey	Grey	Grey

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.